

# SikaGrout<sup>®</sup>-9400

## DECLARATION OF PERFORMANCE No. BE0105/03

<b>1</b>	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:</b>	BE0105/03
<b>2</b>	<b>INTENDED USE/S</b>	EN 1504-6:2006 Anchoring product for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works
<b>3</b>	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich Schweiz
<b>4</b>	<b>AUTHORISED REPRESENTATIVE:</b>	
<b>5</b>	<b>SYSTEM/S OF AVCP:</b>	System 2+ System 4 (Reaction to fire)
<b>6a</b>	<b>HARMONISED STANDARD:</b>	EN 1504-6:2006
	Notified body/ies:	0749

### Declaration of Performance

SikaGrout<sup>®</sup>-9400

BE0105/03

2025.02, ver. 21

1707

---

**7 DECLARED PERFORMANCE/S**

---

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1	System 4	EN 1504-6: 2006
Pull-out strength	Displacement $\leq 0,6$ mm at load of 75 kN	System 2+	
Chloride ion content	$\leq 0,05$ %	System 2+	
Glass transition temperature	NPD	System 2+	
Durability/Creep under tensile load	NPD	System 2+	
Dangerous substances	Comply with 5.3 (EN 1504-6)	System 2+	
Specific Technical documentation:	496/17		
Fulfilled requirements:	Organic content: < 1 % in weight		

---

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 and 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name: Eric Herremans  
Function: Site Manager  
At Ham on 28 February 2025

Name: Bram Thijs  
Function: Laboratory Manager  
At Ham on 28 February 2025



---

End of information as required by Regulation (EU) No 305/2011



24

Sika Services AG, Zurich, Switzerland

BE0105/03

EN 1504-6:2006 Principles 4.2

Notified Body 0749

Anchoring product

Reaction to fire	Class A1
Pull-out strength	Displacement $\leq 0,6$ mm at load of 75 kN
Chloride ion content	$\leq 0,05$ %
Dangerous substances	Comply with 5.3 (EN 1504-6)

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

SikaGrout®-9400  
BE0105/03  
2025.02, ver. 2  
1707

**Sika Services AG**  
Tüffenwies 16-22  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Declaration of Performance**

SikaGrout®-9400  
BE0105/03  
2025.02, ver. 2  
1707

**4/4**

**BUILDING TRUST**

