

Sikadur[®]-31 DW

Declaration of Performance No 35605796

1	Unique identification code of the product-type:	35605796
2	Intended use/es:	For uses in buildings and civil engineering works — Structural bonding products for bonded mortar or concrete as covered in the scope of this standard For uses subject to reaction to fire regulations — Structural bonding products for bonded mortar or concrete as covered in the scope of this standard
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 2+ (For uses in buildings and civil engineering works) System 3 (For uses subject to reaction to fire regulations)
6a	Harmonised standard:	EN 1504-4:2004
	Notified body/ies:	0099, 0370

Declaration of Performance

Sikadur[®]-31 DW

35605796

11/01/2024 2

1053

1 / 3

7 Declared performance/s:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bond/adhesion strength	Fresh concrete to hardened concrete	Pass	System 2+
	Hardened concrete to hardened concrete	Pass	
Shear strength	$\geq 6 \text{ N/mm}^2$		System 2+
Compressive strength	$\geq 30 \text{ N/mm}^2$		System 2+
Shrinkage/expansion	$\leq 0.1 \%$		System 2+
Workability	100 min at 23 °C		System 2+
Sensitivity to water	Pass		System 2+
Modulus of elasticity	$\geq 2000 \text{ N/mm}^2$		System 2+
Coefficient of thermal expansion	$\leq 100 \times 10^{-6}$ per K		System 2+
Glass transition temperature	$\geq 40 \text{ °C}$		System 2+
Reaction to fire	Class C-s2, d0; Class B _{fl} -s1		System 3
Durability	Pass		System 2+
Dangerous substances	NPD		System 2+

EN 1504-4:2004


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski

Function: Corporate Standardisation and Approvals

At Warsaw on 2024-01-11



Name: Wiktor Karpała

Function: Standardisation and Approvals

At Warsaw on 2024-01-11



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikadur®-31 DW

35605796

11/01/2024 2

1053

2 / 3

BUILDING TRUST



CE

23

Sika Services AG, Zürich, Switzerland

35605796

Shear strength	$\geq 6 \text{ N/mm}^2$
Compressive strength	$\geq 30 \text{ N/mm}^2$
Shrinkage/expansion	$\leq 0.1 \%$
Workability	100 min at 23 °C
Modulus of elasticity	$\geq 2000 \text{ N/mm}^2$
Coefficient of thermal expansion	$\leq 100 \times 10^{-6}$ per K
Glass transition temperature	$\geq 40 \text{ °C}$
Reaction to fire	Class C-s2, d0; Class B _{fi} -s1

EN 1504-4:2004

0099, 0370

For uses in buildings and civil engineering works — Structural bonding products for bonded mortar or concrete as covered in the scope of this standard
For uses subject to reaction to fire regulations — Structural bonding products for bonded mortar or concrete as covered in the scope of this standard

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

For information and advice on the safe handling, storage and use of this product, users shall refer to the most recent Product Data Sheet (PDS).

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikadur®-31 DW

35605796

11/01/2024 2

1053

3 / 3

BUILDING TRUST

