

# Sikafloor®-3310

## DECLARATION OF PERFORMANCE

### No. 37608020

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	37608020
2	<b>INTENDED USE/S</b>	Synthetic resin screed for internal uses
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	EN 13813: System 4 (for internal uses)  EN 13813: System 3 (for internal uses subject to reaction to fire regulations)
6a	<b>HARMONISED STANDARD:</b>	EN 13813:2002
	Notified body/ies:	1611

#### Declaration of Performance

Sikafloor®-3310  
37608020  
2021.03 , ver. 1  
1041

**7 DECLARED PERFORMANCE/S** Tested system: Sikafloor®-3200 + Sikafloor®-3310 + Sikafloor®-304 W Matt

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	B <sub>fl</sub>	System 3	EN 13813:2002
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	AR0,5	System 4	
Bond strength:	B2,0	System 4	
Impact resistance:	IR4	System 4	
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski  
 Function: Corporate Standardization and Approvals  
 At Warsaw on 03 March 2021

Name : Tatiana Ageyeva  
 Function: Standardization and Approvals  
 At Warsaw on 03 March 2021




End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikafloor®-3310  
 37608020  
 2021.03 , ver. 1  
 1041





09

EN 13813: 2002

37608020

Sika Services AG, Zürich, Switzerland

Notified Body 1611

Synthetic resin screed for internal uses

Reaction to fire:	B <sub>f1</sub>
Release of corrosive substances:	SR
Wear resistance:	AR0,5
Bond strength:	B2,0
Impact resistance:	IR4

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


## FOR FURTHER INFORMATION:

Sika Services AG  
Tüffenwies 16  
8048 Zürich

Telefon +41-58 436 40 40  
Telefax +41-58 436 53 54  
[www.sika.ch](http://www.sika.ch)

## Declaration of Performance

Sikafloor®-3310  
37608020  
2021.03 , ver. 1  
1041



**Declaration of Performance**

Sikafloor®-3310

37608020

2021.03 , ver. 1

1041

**4/4**

**BUILDING TRUST**

