

PRODUCT DATA SHEET

Sikafloor®-5050 Filler

(formerly MTop 5050 Filler)

Premixed filler.

DESCRIPTION

Sikafloor®-5050 Filler is premixed filler for use in the Sikafloor®-series.

USES

Used as a filler in the Sikafloor®-series:

- Scratch coat primer
- Self-leveling body coat

FEATURES

- Non flammable
- Easy to apply
- Premixed filler with a special aggregate blend

PRODUCT INFORMATION

Composition	Selected quartz fillers.
Packaging	25 kg bag.
Shelf life	Under the specified storage conditions the material has a shelf life of 12 months. For maximum shelf life under these conditions, see "Best before" label.
Storage conditions	Product must be stored in original, unopened and undamaged sealed packaging in dry conditions and in temperatures between 15–25 °C. Protect from frost.
Consumption	<p>Sikafloor®-5050 Filler Consumption</p> <ul style="list-style-type: none">▪ 9,75kg Sikafloor®-5050 Filler to 30kg Sikafloor BC 375 N▪ 11,1kg Sikafloor®-5050 Filler to 20kg Sikafloor-3310▪ 25kg Sikafloor®-5050 Filler to 30kg Sikafloor-264 Plus▪ 6kg Sikafloor®-5050 Filler to 30kg Sikafloor-2350 ESD▪ 20kg Sikafloor®-5050 Filler to 20kg Sikafloor-2510 W

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

MIXING

Please refer to the corresponding flooring system document.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Oy Sika Finland Ab

Koskelontie 23 C

PL 49

02921 Espoo

Puh. + 358 9 511 431

Fax. + 358 9 511 43 300

www.sika.fi



PRODUCT DATA SHEET

Sikafloor®-5050 Filler

December 2025, Version 02.01

02081600000002016

Sikafloor-5050Filler-en-FI-(12-2025)-2-1.pdf