

BUILDING TRUST

Sikafloor[®] QuartzTop-100

DECLARATION OF PERFORMANCE No. BE0066/03

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	BE0066/03
2	INTENDED USE/S	Cementitious floor screed materials for internal uses subject to reaction to fire regulations.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 4
5a	HARMONISED STANDARD:	EN 13813:2002

Declaration of Performance Sikafloor® QuartzTop-100 BE0066/03 2024.04 , ver. 1 1707 6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification	
Reaction to fire	A1fl	System 4		
Release of corrosive substances	СТ	System 4		
Water permeability	NPD	System 4		
Water vapour permeability	NPD	System 4		
Compressive strength	C60	System 4		
Flexural strength	F10	System 4	EN 13813:2002	
Wear resistance	A6	System 4		
Sound insulation	NPD	System 4		
Sound absorption	NPD	System 4		
Thermal resistance	NPD	System 4		
Chemical resistance	NPD	System 4		

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Bram Thies Function: Laboratory Manager At Ham on 22 April 2024

THE

Name : Paul Magera Function: General Manager At Ham on 22 April 2024

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikafloor® QuartzTop-100 BE0066/03 2024.04 , ver. 1 1707



BUILDING TRUST

24

Sika Services AG, Zurich, Switzerland

DoP No. BE0066/03

EN 13813:2002

Cementitious floor screed materials for internal uses subject to reaction to fire regulations

Reaction to fire	A1fl
Release of corrosive substances	СТ
Compressive strength	C60
Flexural strength	F10
Wear resistance	A6

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG

Tüffenwies 16 8064 Zürich Switzerland www.sika.com

Declaration of Performance Sikafloor® QuartzTop-100 BE0066/03 2024.04 , ver. 1 1707



BUILDING TRUST