

Sika® WT-200 P

DECLARATION OF PERFORMANCE

No. 84924988

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	84924988
2	INTENDED USE/S	EN 934-2:2009+A1:2012 Water resisting admixture for concrete (9)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 934-2:2009+A1:2012
	Notified body/ies:	1029

Declaration of Performance

Sika® WT-200 P

84924988

2021.03 , ver. 1

1088

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	$\leq 0.1 \%$	System 2+	EN 934-2: 2009+A1:2012
Alkali content	$\leq 4.0 \%$	System 2+	
Corrosion behavior	Contains approved substances according to EN 934-1: 2008 Annex A1	System 2+	
Compressive strength (Reference I)	Test mix $\geq 85 \%$ of control mix	System 2+	
Air content	Test mix $\leq 2 \%$ above control mix	System 2+	
Capillary absorption	Tested for 7 days after 7 days curing: Test mix $\leq 50 \%$ by mass of control mix	System 2+	
Dangerous substances	NPD	System 2+	
Durability	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization
and Approvals
At Warsaw on 30 March 2021

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 30 March 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika® WT-200 P
84924988
2021.03 , ver. 1
1088



13

Sika Services AG, Zurich, Switzerland

84924988

EN 934-2:2009+A1:2012

Notified Body 1029

Water resisting admixture for concrete (9)

Performance Criteria – Concrete Watertightness		
Test	Value	Source / Standards
Water conductivity	<6 g/m ² /h	Sika AG SIA 262-1 Annex A
Water penetration	<30mm	Sika AG EN 12390 Part 8
Maximum water penetration	5 bar / constant	Sika AG EN 12390 Part 8
Drying shrinkage	<0.5‰	SN 262-1 Annex F
BBA Certificate	Approval	BBA

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika® WT-200 P
84924988
2021.03 , ver. 1
1088

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

Sika® WT-200 P
84924988
2021.03 , ver. 1
1088

